


Oil Skimmers with Timer



This is a copy of McMaster-Carr's web page. Click the part number to follow the link to McMaster-Carr's website

Set your skimmer to operate at specific times. These come with a time-activated on/off switch that can be set in 15 minute increments. Belt is 1" wide. Housing is Type 304 stainless steel and plastic. Motor is continuous duty and operates on 120 volts AC. It has a 6-ft. cord with a three-prong plug. Skimmers include a 2-ft. length of 5/8" ID PVC tubing for discharge.

Standard skimmers require a minimum tank opening of 2"×3". **Skimmers for 55-gallon drums** fit a 2" bung hole.

Belt Lg.	Belt Circumference	Skimmers For 1/4 gph		For 1 gph		Replacement Belts	
		Part No.	Each	Part No.	Each	Part No.	Each
With Polyurethane Belt—Max. temp. is 120° F							
Standard							
8"	27"	44065K41	\$450.85	44065K51	\$479.66	44065K611	\$96.30
12"	36"	44065K42	461.02	44065K52	491.53	44065K612	114.81
18"	48"	44065K43	493.65	44065K53	505.08	44065K613	133.33
24"	60"	44065K44	509.52	44065K54	516.95	44065K614	151.85
For 55-Gallon Drums							
24"	60"	44535K25	585.00	44535K35	594.92	44065K614	151.85
With Type 304 Stainless Steel Belt—Max. temp. is 210° F							
Standard							
8"	27"	4436K11	522.03	4436K21	538.07	4436K71	109.26
12"	36"	4436K12	534.69	4436K22	549.15	4436K72	125.93
18"	48"	4436K13	549.15	4436K23	564.41	4436K73	146.30
24"	60"	4436K14	564.41	4436K24	581.36	4436K74	159.26