



TECHNICAL DATA

Motor: 30 RPM Permanent Magnet Synchronous Motor (10 RPM also available) delivering 64 in-oz of Torque. Die Cast Gear Housing, Cut Brass Gears, Class F Insulation, UL/CSA Recognized, 115/1/60, Draws 0.055 Amps (7 watts)

Housing: Water resistant, clear anodized 6061 aluminum

Mounting Bracket: 14 Gauge Cold Rolled Steel, Powder Coated Black

Scraper: 3/16" heat-resistant, corrosion-resistant alumina washer

Circular Belt or "Tube": 3/16" diameter oleophilic polyurethane cord, 83A durometer. Non-Static & Non-Stretch

Operating Temperatures: polyurethane belts operate effectively up to 120F.

Pulley: Corrosion-Resistant acetal resin (Delrin) with stainless set screw

Power Cord: 16 Gauge, Grounded 10-foot SVT with Three-Pronged Plug, CSA/UL Rated, NEMA 5-15P

Collection Rate: Each customer's condition is different, but our lab tests suggest a collection rate of about ½ gallon per hour (30 RPM) or 0.2 gallons per hour (10 RPM)

Weight: 4.2 lbs without stand, 5.1 lbs with stand

Dimensions: 3" x 4-5/8" x 3-7/8" without stand, 3.75" x 5-1/8" x 6.75" with stand

Assembly Required: No